

Sol 3W 532nm

Spec. #: SL19106

Q-Switched compact ns DPSSL



FEATURES

- _ Up to 200 uJ
- _ Short pulse duration
- _ up to 100 kHz
- _ All solid state design
- _ Air Cooled
- _ Low heat waste

Technical Specifications	Typical	
Output Wavelength	532	nm
Pulse energy	Up to 200	uJ
Pulse Width	15 to 70	ns
Repetition Rate	Single shot to 100	kHz
Polarization	Linear 100:1	
Beam diameter (1/e ²)	< 8 (collimated)	mm
Beam Quality (M ²)	< 2 @ 10 kHz	
Electrical Requirements	24 V DC IN, < 10 A (*)	
Cooling	Air Cooled	
Mechanical Dimensions	235 x 105 x 95	mm ³
Weight	< 4.5	kg

(*) Optional: 100-230 AC DC Power Supply

Options Available:	Applications:
<ul style="list-style-type: none"> - Beam Expanding and Collimating optics - Red aiming beam - Circular polarization - Water and contact cooling 	<ul style="list-style-type: none"> - Specialty Marking - Material Processing - Medical - OLED



All information included in this document is subject to change without notice.

Update data sheets can be provided after formal request.

For complete details, please contact your local **Bright Solutions** sales representative or visit our website at www.brightsolutions.it

Bright Solutions Srl
Via Artigiani, 27
27010 Cura Carpignano - PV
Italy
Ph. +39 0382583094
e-mail: sales@brightsolutions.it