




SPECIALIZING IN QUALITY HIGH-POWER DIODE LASERS

2026 CATALOG **MULTIMODE LASER DIODES**



r×p×m×c
www.rpmclasers.com

Why LDX Optronics?

Your Preferred Source for High-Performance Multimode Laser Diode Products

LDX Optronics is our top choice for high-performance multimode laser diode products. With a wide range of wavelengths and standard packages, along with expertise in packaging and a willingness to customize, they provide optimal solutions for most applications.

More Than 30 Years of Made in the USA Excellence

- All products are proudly manufactured in the USA and shipped from Tennessee, eliminating concerns related to tariffs, international shipping issues, and potential disruptions in supply chains due to global political tensions or trade restrictions.
- Established in 1990, LDX Optronics focuses on high-power multimode laser diodes

Superior Packaging results in Superior Performance

- All products utilize an advanced flux-free & void-free soldering process.
- Customers can choose between hard (AuSn) or soft (In) solder for their products.
- Robust and reliable products that are inherently resistant to shock and vibration.

Proven Quality Process with Unmatched Reliability

- Each wafer design receives extensive qualification and life testing.
- Every device undergoes a thorough burn-in before shipment.
- Each device is individually characterized electrically and optically, with full data supplied with each device.

Customized Laser Diodes for Better Products

- Custom options are available for wavelength, emitter size, and output power. A variety of industry standard laser packages are available, as well as custom package options.
- Additional package options include temperature control (TEC), photodiode, fast axis lensing, or fiber coupling.
- Customers can choose electrically isolated or hermetically sealed options.

Your laser diode partner for your manufacturing business

- Guaranteed supply for the life of your program.
- Extensive selection of wavelengths and package options available from stock, but also open to designing a custom solution for your needs.
- Just-in-time deliveries with buffer stock.

LDX Optronics' management team emphasizes quality and consistency in the semiconductor laser manufacturing processes, with each wafer receiving extensive qualification and life testing, and each device undergoing a thorough burn-in before shipment. Whether you need a custom wafer design or a drop-in replacement that can be integrated into your existing system, LDX Optronics can provide you with a reliable, high-quality product.

445nm - 690nm LASER DIODES

Part Number	Wavelength (nm)	Wavelength Tolerance	Emitter size (microns)	Output Power (mW)	Operating Temp (°C)	Polarization	Packages
LDX-3102-405	405	+/-5 nm	20	1000	25	TE	7, 11, 15,
LDX-3303-445	445	+/-10 nm	30	3500	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3102-520	520	+/-10 nm	15	1000	20	TE	7, 11, 15,
LDX-2106-622	622	+/-3 nm	60	150	5	TE	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-2205-627	627	+/-3 nm	50	250	10	TM	1, 4, 5, 8, 9, 10, 11, 12, 14, 15,
LDX-2310-627	627	+/-3 nm	100	350	10	TM	1, 4, 5, 8, 9, 10, 11, 12, 14, 15,
LDX-2205-630	630	+/-3 nm	50	250	15	TM	1, 4, 5, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2410-630	630	+/-3 nm	100	400	10	TM	1, 4, 5, 8, 9, 10, 11, 12, 14, 15,
LDX-2305-635	635	+/-3 nm	50	300	20	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2410-635	635	+/-3 nm	100	400	20	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2615-635	635	+/-3 nm	150	600	20	TM	1, 4, 5, 8, 9, 10, 11, 12, 14, 15,
LDX-3130-635	635	+/-3 nm	300	1200	15	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-2305-645	645	+/-3 nm	50	350	20	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2710-645	645	+/-3 nm	100	700	20	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2305-650	650	+/-3 nm	50	350	20	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2710-650	650	+/-3 nm	100	700	20	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3115-650	650	+/-3 nm	150	1000	20	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3230-650	650	+/-3 nm	300	2000	20	TE	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-2305-660	660	+/-3 nm	50	350	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2710-660	660	+/-3 nm	100	750	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3115-660	660	+/-3 nm	150	1000	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3230-660	660	+/-3 nm	300	2000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15,
LDX-2305-665	665	+/-3 nm	50	350	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2710-665	665	+/-3 nm	100	750	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3115-665	665	+/-3 nm	150	1000	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3230-665	665	+/-3 nm	300	2000	20	TE	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-2405-680	680	+/-3 nm	50	400	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2810-680	680	+/-3 nm	100	800	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3115-680	680	+/-3 nm	150	1200	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3230-680	680	+/-3 nm	300	2500	25	TE	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-2405-685	685	+/-3 nm	50	400	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2810-685	685	+/-3 nm	100	800	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3115-685	685	+/-3 nm	150	1200	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3230-685	685	+/-3 nm	300	2500	25	TE	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-2405-690	690	+/-3 nm	50	400	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-2810-690	690	+/-3 nm	100	800	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3115-690	690	+/-3 nm	150	1200	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3230-690	690	+/-3 nm	300	2500	25	TE	1, 4, 5, 8, 9, 11, 12, 14, 15,

All values are typical for a device packaged on C-mount, performance may differ with other package options

725nm-792nm LASER DIODES

Part Number	Wavelength (nm)	Wavelength Tolerance	Emitter size (microns)	Output Power (mW)	Operating Temp (°C)	Polarization	Packages
LDX-3105-725	725	+/-5 nm	50	1000	20	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3110-725	725	+/-5 nm	100	1500	20	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3215-725	725	+/-5 nm	150	2000	20	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3105-730	730	+/-5 nm	50	1000	20	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3210-730	730	+/-5 nm	100	2000	20	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3315-730	730	+/-5 nm	150	2500	20	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3330-730	730	+/-5 nm	300	3000	20	TM	1, 4, 5, 9, 11, 12, 14, 15,
LDX-3105-735	735	+/-5 nm	50	1000	25	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3110-735	735	+/-5 nm	100	1750	25	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15,
LDX-3215-735	735	+/-5 nm	150	2000	25	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3315-735	735	+/-5 nm	150	2500	25	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3430-735	735	+/-5 nm	300	4000	25	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3105-740	740	+/-5 nm	50	1500	25	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3210-740	740	+/-5 nm	100	2000	25	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3315-740	740	+/-5 nm	150	3000	25	TM	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15,
LDX-3530-740	740	+/-5 nm	300	5000	25	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3105-750	750	+/-5 nm	50	1200	25	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3110-750	750	+/-5 nm	100	1500	25	TM	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3210-750	750	+/-5 nm	100	2000	25	TM	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15,
LDX-3315-750	750	+/-5 nm	150	3000	25	TM	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15,
LDX-3530-750	750	+/-5 nm	300	5000	20	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3105-760	760	+/-5 nm	50	1200	25	TM	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3210-760	760	+/-5 nm	100	2000	25	TE or TM	1, 4, 5, 6, 7, 9, 10, 11, 12, 14, 15,
LDX-3315-760	760	+/-5 nm	150	3000	25	TE or TM	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3420-760	760	+/-5 nm	200	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3630-760	760	+/-5 nm	300	6000	25	TM	1, 4, 5, 8, 9, 11, 12, 14, 15,
LDX-3315-775	775	+/-3 nm	150	3000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3105-780	780	+/-3 nm	50	1200	25	TM	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3310-780	780	+/-3 nm	100	2500	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3315-780	780	+/-3 nm	150	3500	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3520-780	780	+/-3 nm	200	5000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3315-785	785	+/-3 nm	150	3500	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3520-785	785	+/-3 nm	200	5000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3105-792	792	+/-3 nm	50	1200	25	TM	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3310-792	792	+/-3 nm	100	3000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3415-792	792	+/-3 nm	150	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3820-792	792	+/-5 nm	200	8000	25	TM	3, 5, 9, 11, 12, 14, 15,

All values are typical for a device packaged on C-mount, performance may differ with other package options

797nm-980nm LASER DIODES

Part Number	Wavelength (nm)	Wavelength Tolerance	Emitter size (microns)	Output Power (mW)	Operating Temp (°C)	Polarization	Packages
LDX-3310-797	797	+/-3 nm	100	3000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3415-797	797	+/-3 nm	150	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3520-797	797	+/-3 nm	200	5000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3105-808	808	+/-3 nm	50	1200	25	TE	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3210-808	808	+/-3 nm	100	2000	25	TE	1, 4, 5, 6, 7, 9, 10, 11, 12, 14, 15,
LDX-3310-808	808	+/-3 nm	100	3000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3410-808	808	+/-3 nm	100	4000	25	TM	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3415-808	808	+/-3 nm	150	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 13, 14, 15,
LDX-3610-808	808	+/-3 nm	100	6000	25	TM	3, 5, 9, 11, 12, 14, 15,
LDX-3620-808	808	+/-3 nm	200	6000	25	TE or TM	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3A20-808	808	+/-5 nm	200	10000	25	TM	3, 5, 9, 11, 12, 14, 15,
LDX-3415-825	825	+/-5 nm	150	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3210-835	835	+/-5 nm	100	2000	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15,
LDX-3610-835	835	+/-5 nm	100	6000	25	TM	3, 5, 9, 11, 12, 14, 15,
LDX-3103-860	860	+/-10 nm	30	1000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3105-860	860	+/-10 nm	50	1000	25	TE	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3110-860	860	+/-10 nm	100	1500	25	TE	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3210-860	860	+/-10 nm	100	2000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3310-860	860	+/-10 nm	100	2500	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3315-860	860	+/-10 nm	150	3500	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3520-860	860	+/-10 nm	200	5000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3415-870	870	+/-5 nm	150	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3210-880	880	+/-10 nm	100	2500	25	TE	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3415-880	880	+/-10 nm	150	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3210-905	905	+/-5 nm	100	2500	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15,
LDX-3410-915	915	+/-10 nm	100	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3615-915	915	+/-10 nm	150	6000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3A10-915	915	+/-10 nm	100	10000	25	TE	3, 5, 9, 11, 12, 14, 15,
LDX-3410-940	940	+/-10 nm	100	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3615-940	940	+/-10 nm	150	6000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3810-940	940	+/-10 nm	100	8000	25	TE	3, 5, 9, 11, 12, 14, 15,
LDX-3F20-940	940	+/-10 nm	200	16000	25	TE	3, 5, 9, 12, 14, 15,
LDX-3A10-960	960	+/-10 nm	100	10000	25	TE	3, 5, 9, 11, 12, 14, 15,
LDX-3105-980	980	+/-10 nm	50	1500	25	TE	1, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15,
LDX-3410-980	980	+/-10 nm	100	4000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3615-980	980	+/-10 nm	150	6000	25	TE	1, 4, 5, 6, 7, 9, 11, 12, 14, 15,
LDX-3A10-980	980	+/-10 nm	100	10000	25	TE	3, 5, 9, 11, 12, 14, 15,

All values are typical for a device packaged on C-mount, performance may differ with other package options

1015nm-1900nm LASER DIODES


Part Number	Wavelength (nm)	Wavelength Tolerance	Emitter size (microns)	Output Power (mW)	Operating Temp (°C)	Polarization	Packages
LDX-3C20-1015	1015	+/-5 nm	200	12000	25	TE	3, 5, 9, 11, 12, 14, 15,
LDX-3310-1030	1030	+/-10 nm	100	3000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15
LDX-3520-1030	1030	+/-10 nm	200	5000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3C20-1030	1030	+/-5 nm	200	12000	25	TE	3, 5, 7, 8, 9, 11, 12,
LDX-3105-1064	1064	+/-10 nm	50	1500	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12,
LDX-3410-1064	1064	+/-10 nm	100	4000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3515-1064	1064	+/-10 nm	150	5000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3A10-1064	1064	+/-10 nm	100	10000	25	TE	3, 5, 7, 8, 9, 11, 12,
LDX-3C20-1064	1064	+/-5 nm	200	12000	25	TE	3, 5, 7, 8, 9, 11, 12,
LDX-3205-1130	1130	+/-20 nm	50	2000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3310-1130	1130	+/-20 nm	100	3500	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3515-1130	1130	+/-20 nm	150	5000	25	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3105-1210	1210	+/-20 nm	50	1500	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3210-1210	1210	+/-20 nm	100	2000	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3718-1280	1280	+/-20 nm	180	7000	20	TE	2, 4, 5, 7, 8, 9, 11, 12,
LDX-3310-1370	1370	+/-20 nm	100	3500	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3510-1370	1370	+/-20 nm	100	5000	20	TE	2, 4, 5, 7, 8, 9, 11, 12,
LDX-3310-1470	1470	+/-20 nm	100	3500	25	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3510-1470	1470	+/-20 nm	100	5000	25	TE	2, 4, 5, 7, 8, 9, 11, 12,
LDX-3718-1470	1470	+/-20 nm	180	7000	25	TE	2, 4, 5, 7, 9, 11, 12,
LDX-2803-1550	1550	+/-20 nm	35	800	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3105-1550	1550	+/-20 nm	50	1000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3110-1550	1550	+/-20 nm	100	1500	25	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3205-1550	1550	+/-20 nm	50	1750	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3210-1550	1550	+/-20 nm	100	2500	25	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3310-1550	1550	+/-20 nm	100	3500	25	TE	2, 4, 5, 7, 8, 9, 11, 12,
LDX-3518-1550	1550	+/-20 nm	180	5000	20	TE	2, 4, 5, 7, 9, 11, 12,
LDX-3115-1620	1620	+/-20 nm	150	1000	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3120-1640	1640	+/-20 nm	200	1200	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3210-1675	1675	+/-20 nm	100	2000	20	TE	2, 4, 5, 7, 8, 9, 11, 12,
LDX-3110-1850	1850	+/-30 nm	100	1000	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-2606-1900	1900	+/-10 nm	60	600	20	TE	1, 4, 5, 7, 8, 9, 11, 12,
LDX-3C20-1015	1015	+/-5 nm	200	12000	25	TE	3, 5, 9, 11, 12, 14, 15,
LDX-3310-1030	1030	+/-10 nm	100	3000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15
LDX-3520-1030	1030	+/-10 nm	200	5000	25	TE	1, 4, 5, 6, 7, 8, 9, 11, 12,
LDX-3C20-1030	1030	+/-5 nm	200	12000	25	TE	3, 5, 7, 8, 9, 11, 12,
LDX-3105-1064	1064	+/-10 nm	50	1500	25	TE	1, 4, 5, 6, 7, 8, 9, 10, 11, 12,

All values are typical for a device packaged on Cmount, performance may differ with other package options

LDX follows a policy of continuous product improvement. **Specifications are subject to change without notice.**

These components do not comply with the Federal Regulations (21 CFR Subchapter 1) as administered by the Center for Devices and Radiological health. Purchaser acknowledges that his/her products must comply with these regulations before they can be sold to a customer.

Part Numbering System



Examples:

LDX-3115-680-9	Semiconductor Laser Diode, 680±3 nm, 1200mW, 150um emitter, 9mm Package
LDX-2405-690-BFC-105	Semiconductor Laser Diode, 690±3 nm, 400mW, 50um emitter, Pigtailed Fiber Coupled 8-pin BFC Package w/ >80% Output Power from Fiber, Includes 105um, 0.22NA, 1m long fiber pigtail with SMA connector
LDX-2410-645-B-L1	Semiconductor Laser Diode, 645±5 nm, 400mW, 100um emitter, B-mount w/ FAC Lensing, Best Collimation
LDX-2710-660-HHL-L2	Semiconductor Laser Diode, 660±3 nm, 750mW, 100um emitter, HHL Package w/ TEC, PD, Thermistor, FAC Lens, Squared Beam

Package & Options

Free Space Package - Exposed Emitter					
#	Package Name		Features	Options	Drawing
1,2,3	C-Mount Package		Small footprint with screw mounting Material – Copper (OFHC) Fast-axis lensing	Fast-axis lensing	
4	B-Mount Package		Very small footprint Material – Copper (Cu)	Fast-axis lensing	
5	Chip-on-Submount		Very small footprint Material – Aluminum Nitride (AlN) / Beryllium Oxide (BeO)	Fast-axis lensing	

Free Space Package - Hermetically Sealed Windowed Packages					
#	Package		Features	Options	Drawing
6, 7, 8	9mm Package		Industry-standard package Header – Copper	Photodiode, Isolated package, Fast-axis lensing	
9, 10	TO-3 Package		Mounting to heatsink with screws Header – Copper	TEC, Thermistor, Photodiode, Fast-axis lensing	
11	HHL Package		Internal peltier cooler (TEC), thermistor, and photodiode Baseplate material – Copper Tungsten (CuW)	Fast-axis lensing	

FAC Lensing Options:		
Best Collimation	L1	Less than 1° divergence in the fast axis direction.
Squared Beam FAC	L2	Matches the fast-axis to the slow-axis divergence.

Fiber Coupled Packages - Hermetically Sealed					
#	Package		Features	Options	Drawing
12	9mm SMA FC Package		Industry-standard package SMA connector for detachable fiber Header – Copper	Photodiode, Isolated package	
13	8-Pin BFC Package		Fiber pigtail with SMA connector Baseplate material – Copper	TEC, Thermistor, Photodiode	
14	2-Pin FCP Package		Fiber pigtail with SMA connector Baseplate material – Copper	none	
15	HHL-FC Package		Fiber pigtail with SMA connector Internal TEC, thermistor, and PD Baseplate material – Copper Tungsten (CuW)	none	

Emitter Size (μm)	Standard Fiber size (μm)
≤ 80	105
100	105 or 200
150	200
200	200 or 365
300	365

General Precautions

1. Special wavelength diodes (especially red diodes) are much, much more susceptible to damage than standard infrared diodes.
2. Think about how you are employing the diodes to make sure you are doing everything possible to get a long lifetime. We want you to be successful using these products.
3. Keep the diodes *clean*. They should not be operated in an environment where dust particles in the air can reach the active region (output facet) of the diode.
4. Keep the output facet (which emits light) *dry*. If you store the unit in a high humidity, the optical coatings can be damaged and render the diode useless.
5. Operating the laser diode at a *temperature lower* than recommended will usually slightly increase the output power (higher efficiency) and improve lifetime.
6. Operating the laser diode at a *temperature higher* than recommended will increase the threshold current and decrease the slope efficiency.
7. Laser diodes need to be operated with an *approved power supply/driver* or they may be damaged and/or destroyed quickly. Off-the-shelf drivers can deliver a high spike of current at turn-on, and they can deliver a very short duration reverse biasing when the unit is turned off. Either of these will damage and/or destroy the diode laser.
8. The power supply/driver should be current-regulated and specifically designed for laser diodes. The power supply should create no surges or spikes, no reverse voltages and should not have any ringing. Many poorly designed power supplies have voltage transients during turn-on, turn-off, or in the case of power failure.
9. Never make the connection to the laser diode with the power supply voltage on. Most laser diode power supplies have provision to disable the supply and short the output to allow for connection of the diode.
10. Laser diodes are very sensitive to damage by electrostatic discharge (ESD), or other voltage transients. The laser should be handled using static-safe procedures when it is taken out of its static-protective shipping container. When the laser is not connected to a power supply, the user should short the anode and cathode together to prevent static damage.
11. Some laser diodes are susceptible to damage from *back reflections* into the device. This is more the case with shorter wavelength material than with longer wavelengths. Thus, if attempting to collimate the output, care must be taken to avoid back reflections.
12. The emission wavelength changes with temperature: the wavelength changes about +1 nm for every 6° C increase in temperature. This value varies by wavelength.

LDX follows a policy of continuous product improvement. **Specifications are subject to change without notice.**

These components do not comply with the Federal Regulations (21 CFR Subchapter 1) as administered by the Center for Devices and Radiological health. Purchaser acknowledges that his/her products must comply with these regulations before they can be sold to a customer.

Thermal Management

1. *Heat*: This is the biggest cause of field failures.
2. Some laser diodes are more sensitive than others to the operating temperature. Red laser diodes tend to be more temperature sensitive than the infrared laser diodes.
3. Many customers do not appreciate the importance and/or the complexity of removing waste heat.
4. Because operating temperature has a strong influence on laser lifetime, the heatsinking of the laser package is of tremendous importance and doing it well is not as simple as many assume it is.
5. Waste heat must be removed efficiently and instantaneously, or the laser will heat up and burn out, or, at a minimum, experience an abbreviated lifetime.
6. The laser can be operated at higher temperatures than recommended, but the lifetime of the laser is reduced exponentially as the operating temperature is increased.
7. The diode package should be attached to a heatsink plate at least several millimeters thick.
8. The heatsink must be capable of dissipating the waste heat generated by the laser diode. High power laser diodes are typically 10 – 50% efficient at converting electricity into light. The remainder of the electrical input power is dissipated as heat. Therefore, there may be several watts of waste heat generated by the laser. Because so much heat is generated within the small area, it is critical that the laser is securely connected to an adequate heatsink
9. The best heatsink material is copper, but aluminum is also a fair heat conductor. If aluminum is used, the surface should not be anodized in the region where the laser package makes contact with the heatsink. The aluminum oxide anodized coating makes an effective thermal insulator.
10. The surface of the heatsink should be machined flat and smooth where it will contact the back of the laser package to allow for efficient heat transfer.
11. Thermal compound, or an indium foil washer can be used to reduce the thermal impedance of this interface. Our experience is that indium foil offers negligible improvement over a good copper-to-copper interface. In permanent installations, some improvement of the heatsinking can be achieved using a silver-filled epoxy at this interface. If silver-filled epoxy is used, it should be a “space qualified” low outgassing formulation to avoid contamination of the laser facets (Epoxy Technology H21D, for example)
12. The heatsink may be cooled by air, water, or thermoelectric coolers. Depending on the type of laser, an air-cooled heatsink may provide sufficient cooling, as long as the application does not require stability of the laser wavelength and output power. Most often, active cooling of the heatsink must be used. Active cooling usually is either water-cooling, or thermoelectric coolers (TEC's).
13. Finally, when testing out a heatsink configuration, it is wise to test the temperature drop between the laser package and the heatsink using a very small thermocouple touched against the base of the package. The temperature drop during laser operation should be only 1-2 ° C.

Free Space Packages

Free space packages can be either a simple open heatsink with an exposed laser chip or a sealed TO-can type package. With open heatsinks, there is no protection for the delicate laser chip. The laser chip is very fragile and must be protected from any mechanical contact. The exposed laser facets (mirror coatings) must not be contaminated with any foreign material. Facet contamination can cause immediate and permanent damage to the laser. You should not blow on the laser, or expose the laser to smoke, dust, oils, or adhesive fumes.

The laser facets are sensitive to accumulation of dust. When the laser is operating, dust particles tend to be attracted to the laser facet. As the dust particles enter the intense optical field at the laser facet, they burn, and the residues accumulate in the laser facet. Unless the laser is operated in a true "class 100" clean-room environment, this dust accumulation will occur, even in a seemingly clean "lab environment. This kind of contamination does not occur very rapidly, but over several hundred hours of operation in a normal room environment, an open heatsink laser will show tiny "specks" on the lasers facet under microscopic examination. These will gradually degrade the laser prematurely. If an open heatsink laser is to be operated outside of a clean-room for more than short periods, it should be packaged within a sealed container to prevent this dust accumulation. This does not require a true hermetic sealing of the laser. An epoxy seal or O-ring seal around the laser assembly is perfectly sufficient.

Tech Notes:

[AN-01 C-Mount Handling](#)

[AN-02 Laser Chip Information](#)

[AN-03 Laser Emission and Focusing](#)

[AN-04-HHL Package Handling](#)

[AN-06-HHL Package Connectors](#)

[AN-07 9mm Package Handling](#)

[AN-09 TO-3 Package Handling](#)

[AN-10 TO-3 Package Connectors](#)

[AN-12 Monitor Photodiodes](#)

[AN-13 Reverse Protection Diode](#)

[AN-14 Laser Damage from Loose Cabling](#)

[AN-15 Laser Damage from Optical Feedback](#)

[AN-16 Laser Overshoot and Soft Start](#)

Fiber Coupled Packages

Fiber coupled laser diode packages integrate the laser chip with an optical fiber to efficiently deliver the laser output to a specific location or system. These packages typically consist of a laser diode mounted on a heatsink or within a sealed housing, with the emitted light coupled into an optical fiber using precise alignment techniques. The fiber coupling protects the laser facets from direct exposure to environmental contaminants such as dust, smoke, oils, or adhesive fumes, which could otherwise damage the delicate mirror coatings.

The output end of the optical fiber in these packages is sensitive to environmental factors. During operation, dust or particles near the fiber output can scatter the emitted light, reduce beam quality or cause localized heating that may damage the fiber tip. For long-term reliability, the fiber output should be protected with a clean cap or cover when not in use.

Tech Notes:

[AN-05 HHL \(Fiber\) Package Handling](#)

[AN-08 9mm SMA Package Guidelines](#)

[AN-11 BFC, FCP Fiber Package Connectors](#)

[AN-12 Monitor Photodiodes](#)

[AN-13 Reverse Protection Diode](#)

[AN-14 Laser Damage From Loose Cabling](#)

[AN-15 Laser Damage From Optical Feedback](#)

[AN-16 Laser Overshoot and Soft Start](#)

Distributors

China

NewOpto Corporation

Xihu District, Hangzhou 310030, China
Phone: (+86) 188 5711 5252
Email: Sales@NewOpto.com
Website: www.NewOpto.com

Photonteck

Nanshan District, Shenzhen
Guangdong, P.R.China
Tel : 86-755-86170157
86-755-86170157
Fax : 86-755-86170153
Email: info@photonteck.com
Website: www.photonteck.com

Germany / Austria / Switzerland

FLC-Frankfurt Laser Company

GmbH

An den 30 Morgen 13
D-61381 Friedrichsdorf
Germany
Telephone: 49.(0)6172.27978-0
Fax: 49.(0)6172.27978-10
E-Mail: sales@frlaserco.com
Website: www.frlaserco.com

Israel

Bitel Technologies Ltd.

YEHUD, Israel
Telephone: 972.3.6322655
Fax: 972.3.6322279
E-Mail: info@bitel.co.il
Website: <http://www.bitel.co.il/>

Japan

Electronics Optics Research (EOR)

Tokyo 166-0003, Japan
Tel +81-3-3314-5699
Fax +81-3-3314-2333
E-Mail: endoh@eor.jp
Website: www.eor.jp

Optronscience, Inc.

Tokyo 112-0003 Japan
TEL +81-3-5800-1341
FAX +81-3-5800-1342
E-mail: nori_aoyagi@opt-ron.com
Website: <http://www.opt-ron.com/>

M Square Corp.

Tokyo 101-0051 Japan
Telephone: 81.3.3294.0560
Fax: 81.3.3294.0563
E-Mail: info@mxmco.com
Website: www.mxmco.com

Kokyo, Inc.

Kyoto, 600-8411, Japan
Telephone: +81-70-6925-5558
Local: 070-6925-5558
E-Mail: info@symphotony.com
Website: www.symphotony.com/

Keystone International Co., Ltd.

13-27 Sakasai Kashiwa
Chiba 277-0042 JAPAN
Tel.+81-(0)4-7175-8810
Fax.+81-(0)4-7175-5669
E-mail: ohno@keystone-intl.co.jp
Website: www.keystone-intl.co.jp

Korea

LMV Technologies Inc.

#1301 U-Tower, 767 Sinsu-ro
Suji-gu, Yongin-si
Gyeonggi-do
16827
Republic of Korea
Tel 82 31 478 3620
Fax 82 31 478 3624
E-Mail: lvitech@lvitech.com
Website: www.lvitech.com/

Singapore

Acexon Technologies Pte. Ltd.

21 Bukit Batok Crescent
Singapore 658065
Tel: 65-6565-7300
Fax: 65-6565-7005
Email: sales@acexon.com
Website: <http://www.acexon.com/>

Taiwan

CORREMAX International Co., Ltd.

Taipei City, 110, Taiwan
R.O.C.
Telephone : 886.2.2345.2929
Fax: 886.2.2345.0606
E-Mail: info@corremax.com.tw
Website: www.corremax-taiwan.com.tw

United Kingdom

AP Technologies Company

Bath BA2 1RL
Telephone: (0)1225 780400
Fax: (0)8701 266449
E-Mail: info@aptechnologies.co.uk
Website: www.aptechnologies.co.uk

Why RPMC Lasers

As your trusted laser partner, RPMC Lasers simplifies your journey by reducing stress, saving time, and guiding you to the ideal laser solution for your next project. Our skilled team of product and account managers leverages deep expertise to ensure you find the perfect laser for any application—backed by three decades of experience and strong ties with industry-leading manufacturers.

Our Expertise:

- 30+ years of providing expert advice and reliable support
- In-depth knowledge of diode lasers, CW and pulsed lasers, and laser amplifiers
- Long-term partnerships with top-tier laser manufacturers
- Custom solutions tailored to your specific needs
- Extensive experience with certifications in the Medical and Defense industries

What We Offer:

- A small-team approach delivering personalized attention, fast honest answers, and a single point of contact for a seamless experience
- Access to 10,000+ standard laser diodes and solid-state lasers, with 100+ lasers in stock and ready to ship
- Competitive pricing at the manufacturer's standard rates, including full warranties
- U.S.-made solutions for most applications
- High-capacity manufacturing for large-scale projects
- Direct collaboration with the manufacturer's engineering team to tackle your toughest challenges
- Access to the manufacturer's application lab and demo units if available

RPMC Lasers is your go-to source for high-quality laser solutions. Whether you need off-the-shelf lasers, customized solutions, or expert guidance, we are committed to delivering the right laser at the right price for your application.

RPMC Lasers—The Lasers You Need from the People You Trust.